



性能:

额定电流: 5.0A

额定电压: 30V

耐电压: 500V

接触电阻: 30mΩ MAX

绝缘电阻: 500MΩ

工作温度: -55℃~+125℃

使用寿命: 10000次以上

塑件(材质): LCP黑色

接触点(材质): 黄铜C2680, 接触面镀金3U"

RECOMMENDED PCB LAYOUT

TOP VIEW(.XX±0.05)

规格	DIM A	DIM B
BC-0-208	7.0	5.0
BC-0-311	10.5	8.5
BC-0-411	14.0	12.0
BC-0-509	17.5	15.5
BC-0-609	21.0	19.0
BC-0-705	24.5	22.5
BC-0-805	28.0	26.0

NO.	PARTS	MATERIAL	QTY.	FINISHING
2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	BRASS	3	Au PLATED

东莞市朗顿电子科技有限公司

PART NAME		CONNECTOR		DRAWING	G.B.Wu	DWG.No.	DS-BC-195
PART NO.		BC-0-208 311 411 509 609 705 805		CHECK	Q.L..Dai	REV.	A0
	UNIT :	TOLERANCE	UP TO 5	±0.2	APPROVAL	DATE	07-07-2025
	mm	OTHERWISE	ABOVE 5 & 30	±0.3		ANGLE	PAGE

COPYRIGHT RESERVED, PLEASE DO NOT COPY.