



性能:

- 额定电流: 5.0A
- 额定电压: 30V
- 耐电压: 500V
- 接触电阻: 30mΩ MAX
- 绝缘电阻: 500MΩ
- 工作温度: -55℃~+125℃
- 使用寿命: 10000次以上
- 塑件(材质): LCP黑色
- 接触点(材质): 黄铜C2680, 接触面镀金3U"

规格	DIM A	DIM B
BC-0-208	7.0	5.0
BC-0-311	10.5	8.5
BC-0-411	14.0	12.0
BC-0-509	17.5	15.5
BC-0-609	21.0	19.0
BC-0-705	24.5	22.5
BC-0-805	28.0	26.0

RECOMMENDED PCB LAYOUT
TOP VIEW (XX±0.05)

2	HOUSING	LCP	1	BLACK
1	CONTACT TERMINAL	BRASS	3	Au PLATED
NO.	PARTS	MATERIAL	QTY.	FINISHING

东莞市朗顿电子科技有限公司

PART NAME	CONNECTOR		DRAWING	G.B.Wu	DWG.No.	D5-BC-185
PART NO.	BC-0-208 311 411 509 609 705 805		CHECK	Q.L.Doi	REV.	A0
UNIT	mm		APPROVAL		DATE	07-07-2025
SCALE	2:1		PAGE	1 OF 1		

COPYRIGHT RESERVED, PLEASE DO NOT COPY.