



性能:

- 额定电流: 5.0A
- 额定电压: 30V
- 耐电压: 500V
- 接触电阻: 30mΩ Max
- 绝缘电阻: 500MΩ Min
- 工作温度: -40℃~+85℃
- 塑件(材质): LCP
- 接触点(材质): 磷铜, 触点镀金3U",
- 使用寿命: 5000次以上

RECOMMENDED PCB LAYOUT
TOL:(±0.05)

2	HOUSING	LCP	1	BLACK			
1	CONTACT TERMINAL	PHOSPHOR BRONZE	3	Au PLATED			
NO.	PARTS	MATERIAL	QTY.	FINISHING			
PART NAME		CONNECTION	DRAWING	G.B.Wu	DWG.No.	DS-BC-106	
PART NO.		BC-1-211A	CHECK	Q.L.Dai	REV.	A0	
UNIT :		TOLERANCE	UP TO 5	±0.2	APPROVAL	DATE	15-08-2017
mm		OTHERWISE	ABOVE 5~30	±0.3	SCALE	PAGE	1 OF 1
			ABOVE 30	±0.5			
			ANGLE	0°±3'			

东莞市朗顿电子科技有限公司

COPYRIGHT RESERVED, PLEASE DO NOT COPY.